ROLLBAG™ 1075-S

The **Rollbag™ 1075-S** is the most productive, price performing automatic tabletop rollbag system in its class. This machine is compact, with a full color touch screen display and utilizes **Rollbags™** (pre-opened bags-on-a-roll). This tabletop bagger can fill and seal bags significantly faster than manual packaging whether using manual or automated feeding systems.

The **Rollbag 1075-S** is the ultimate in reliability and ease of operation. It's quick to set-up, easy to operate, fast and reliable for hand loading, semi-automatic or fully automatic bag packaging. With the **Rollbag 1075-S**, size changes are accomplished in less than a minute utilizing **Rollbags**. This bagger has an optional thermal transfer printer for printing barcodes, graphics or text. The **1075-S** can also be interfaced with automatic counters, scales and other in-feed devices.

FEATURES & BENEFITS

- Large user friendly color touch screen
- Automatically indexes and opens bag for quick product loading
- Jaw obstruction detection for operator safety
- Capable of up to 60 packages per minute
- Integrated printer controls accessible through HMI with basic print formats built in
- Programmable time delay for pace control or ease of integration with automatic feeding devices
- Industrial, compact tabletop design
- Capable of strip packaging
- Job storage capability for up to 20 jobs
- Designed to meet CE requirements

Optional loading funnel

Optional loading in-feed conveyor



Quick and easy bag changes

OPTIONS & ACCESSORIES

- Seal flatteners, bag deflators and standard or custom supports to ensure clean, straight, retail package seals
- In-feed conveyors help with kit packaging and/or product counting operations
- Automatic counters, scales and other in-feed devices
- Thermal transfer graphic printer up to 4" wide x variable length
- Articulating bag support shelf for heavy products
- Standard or custom funnels to assist with product handling
- Product load tray with optional dividers for sorting and loading parts or kits
- Adjustable height stand
- Photo eye to trigger the bagger
- Dual palm buttons for added operator safety
- 220V, 50/60 Hz operation

SPECIFICATIONS

Speed	Dry cycle speed is over 60 bags/min
Bag Width	2" - 10" *(50mm - 255mm)*
Bag Length	3" - 20" *(75mm - 510mm)*
Feed Rate	up to 30" inches/seconds *(762mm)*
Dimensions	30"L x 26.5"W x 21.5" H*(710x 610 x 545mm)*
Air	80 psi @ 2-5 CFM *(5.5 bar @ 140 l/m)*
Electrical	115V, 7 amp, 50/60 Hz
Weight	75 lbs *(34 kg)*

CLAMCO

Member of PAC Machinery Group

775 Berea Industrial Pkwy., Berea, OH 44017 | 216-267-1911 | sales@clamcopackaging.com | www.clamcopackaging.com