

SURFACE PRINTABLE HOTMELT PACKAGING TAPES

PRINTABLE HP

Our premium HP Carton Sealing Tape is now directly printable.

Your product speaks for itself. Don't let an unreliable tape distort its message.

When a client receives a product from you, its packaging says a great deal about what's waiting inside. Why let a poorly constructed tape get in the way of making a great first impression? With our Surface Printable HP Series, you can rest assured that all text and graphics will come through loud and clear – from hot off the printer to final delivery. From its rapid dry time to its ability to run at full line speeds, the Printable HP Series is designed with efficiency in mind.

This series also offers the highest level of shear strength available, so you know that the contents will arrive safely and securely. With the clearest prints and the strongest holds, place the strength of your brand and the quality of your product in our hands. **Insist that your printer converter uses only Surface Printable HP.**

Relax and unwind a roll from the Printable HP Series.

NOW AVAILABLE - Printable Glass Strapping!



Shurtape®

www.shurtape.com 1.888.442.TAPE

SURFACE PRINTABLE HOTMELT PACKAGING TAPES



HP 260 PRINTABLE HOTMELT OPP



- For use on Siat L33, L36, L233 (or equivalent) printing presses
- Directly printable with all leading brands of solvent inks
- Exclusive release coat technology
- Superior ink anchorage without pickoff
- Quiet off the roll

Tensile Strength	27 lbs/in width
Adhesion to Stainless Steel	44 oz/in width
Thickness	1.9 mils
Elongation	150 %
Application Temperature Range	35° to 110° F

HP 460 PRINTABLE HOTMELT OPP



- For use on Siat L33, L36, L233 (or equivalent) printing presses
- Directly printable with all leading brands of solvent inks
- Exclusive release coat technology
- Superior ink anchorage without pickoff
- Quiet off the roll

Tensile Strength	33 lbs/in width
Adhesion to Stainless Steel	54 oz/in width
Thickness	2.5 mils
Elongation	150 %
Application Temperature Range	35° to 110° F

HP 560 PRINTABLE HOTMELT OPP



- For use on Siat L33, L36, L233 (or equivalent) printing presses
- Directly printable with all leading brands of solvent inks
- Exclusive release coat technology
- Superior ink anchorage without pickoff
- Quiet off the roll

Tensile Strength	42 lbs/in width
Adhesion to Stainless Steel	58 oz/in width
Thickness	3.0 mils
Elongation	150 %
Application Temperature Range	35° to 110° F

GS 496 NOW AVAILABLE! PRINTABLE GLASS STRAPPING



- For use on Siat L33, L36, L233 (or equivalent) printing presses
- Directly printable with all leading brands of solvent inks
- Exclusive release coat technology
- Superior ink anchorage without pickoff
- Quiet off the roll

Tensile Strength	100 lbs/in width
Adhesion to Stainless Steel	72 oz/in width
Thickness	4.5 mils
Elongation	150 %
Application Temperature Range	35° to 110° F