



Case Sealer

LD-16A


Case Sealing for the Real World

This reliable case sealer for industrial environments seals a wide range of cases.

Little David delivers packaging equipment that works for you



Patented kicker adjustment is automatic



The LD-16A offers:

- ☒ Low maintenance
- ☒ Safe UL listed
- ☒ Quick payback
- ☒ Simple 3-adjustment operation
- ☒ Interchangeable tape cartridges
- ☒ Heavy duty steel construction
- ☒ Reliable 24/7 operation

The LD-16A replaces:

- ☒ Expensive labor
- ☒ Hand taping boxes
- ☒ Unsafe machinery

Little David LD-16A



LITTLE DAVID




www.loveshaw.com

LD-16A

Dimensions:

LD-16A:



Additional Case Sealer Models:

Also Available Uniform Legend:

- Semi-automatic case sealer
- Seals top and bottom of uniform box sizes



Also Available LD-16R:

- Fully automatic case sealer
- Seals top and bottom of random sized boxes



Options of the LD-16A:

- Special paints, lacquer, enamel, epoxy, special colors, and stainless steel
- Spare pressure sensitive tape cartridge
- Spare parts kit
- Other conveyor heights available
- 3 phase electrics & NEMA 4
- Customization to extend standard case range capacity

Distributor Information:

Features of the LD-16A:

Reliable Performance - Warranty:

- 1 Year Motor*
- 2 Years Gear Reducer
- 3 Years Cartridge*

*Moving and wear parts are not included. Other restrictions may apply. Consult Loveshaw or your authorized Little David® Distributor for details

Flexible:

- Tapes boxes in a variety of sizes (see below)
- Can be ordered for 2" or 3" wide tape

Easy Operation:

- Plug in operation
- Minimal operator training required
- Sealed drive system
- CaseLocker ST® tape cartridge requires no lubrication

Safe:

- UL listed
- Safety doors automatically shut down machine when opened
- Knife guard system of the CaseLocker ST® tape cartridge only allows the blade to be exposed when the rollers have been depressed

Specifications of the LD-16A:

Note: LD16-A also comes in a B version for larger cases sizes.

Power Requirements:

- 110 VAC, 60 Hz, single phase, 10 Amps

Note: Other voltages available. Contact Loveshaw for details.

Air Requirements:

- 4 SCFM @ 70 psi

Operating Speed:

- Continuous belt drive; 80 per minute (24.4 m/min.)(production rate depends on box size & operator dexterity)

Weight:

- LD-16A: 650 lbs (295 kg) uncrated
- LD-16B: 850 lbs (386 kg) uncrated

Case Capacity: (LD-16A standard with 2" wide Caselocker ST® Cartridge)(LD-16B standard with 3" wide Caselocker ST® Cartridge)

Length: LD-16A: 8" (203mm) - 24" (610mm)
LD-16B: 8" (203mm) - 36" (914mm)

Width: LD-16A: 5" (127mm) - 20" (508mm)
LD-16B: 7" (178mm) - 26" (660mm)

Height*: LD-16A: 4-1/2" (114mm) - 20" (508mm)
LD-16B: 4-1/2" (114mm) - 30" (762mm)

*Optional 3-1/2" (89 mm) minimum box height available

LOVESHAW
an ITW Company

Route 296, Box 83
South Canaan, PA 18459
Tel: (570) 937-4921 Fax: (570) 937-3229
(800) 572-3434

LOVESHAW Europe
A Division of ITW Ltd.

Unit 9 Brunel Gate,
West Portway Industrial Estate
Andover, Hampshire England SP 10 3 SL
Tel: (1264) 357511 Fax: (1264) 355964



©Loveshaw, an ITW Company, 2004