

i tape with



Shown with optional exit table & casters

RSA 3036-SB

Random Semi-Automatic Case Sealer

Interpack's RSA Series Case Sealers are operator-fed machines that automatically adjust for each size case processed. An Interpack™ random case sealer is your solution when production has a need for different sized cases to be processed through a single case sealer.

These machines are engineered to provide:

- Industry leading features
- Heavy duty construction for 24/7 operation
- Ergonomic, user friendly operation

Every Interpack™ case sealer comes with a HSD 2000-ET II tape head with adaptive technology to provide optimal tape application and wipe down to each of the 3 taped panels of the case.

Specifically designed to process a larger range of cases, this oversized side belt drive random case sealer contains the same package of features and benefits as the standard sized RSA 2024-SB. Construction is reinforced to handle larger, heavier cases. Standard 4" tall drive bases provide twice the gripping power.

When you compare features, benefits and value, Interpack™ Case Sealers are the right choice for operators, plant engineers, maintenance and purchasing.

FEATURES & BENEFITS:

- Heavy duty construction will process up to 85 lb cases with dual columns for maximum processing stability
- 4" tall drive bases standard
- 2 modes of operation
 - Upper head retained random mode
 - Bottom only seal mode
- Pneumatic infeed gate assures proper positioning of the case during processing and drastically reduces jams
- Twin 1/3 HP high torque gear motors process larger, heavier cases
- Self-tensioning, self-tracking belt drive simplifies belt replacement
- Offset tape heads process cases as low as 5"
- Unique "Clear" push button to clear jams and replace bottom tape roll

Scan for more information on Interpack's RSA Series, including CAD drawings, manuals and videos!



RSA 3036-SB

SPECIFICATIONS

Model	Min Case (L x W x H)	Max Case (L x W x H)	Case Weight	Belt Speed	Electric	Tape Width	Conveyor Height	Machine Weight	Machine Dimensions (L x W x H)
RSA 3036-SB	6" x 5¼" x 5"	Inf x 30" x 36"	0 - 85 lbs	82 ft/min	110v., 1ph., 60hz., 6A., (2 x ½ HP)	48 - 72 mm (2" - 3")	24" - 30"	816 lbs crated	44½" x 47½" x 83"



Tip up top tape head simplifies roll replacement



Optional random top squeezers compress major flaps



Offset 3" wide tape heads process cases as low as 5"



Twin ½ HP gear motors to process up to 85 lb cases



Selectable top & bottom or bottom only modes



Shown with optional exit table & casters



Digital pneumatics to improve throughput speed



Standard 4" tall side belts



Self-tensioning & self-tracking drive belts simplify belt replacement



Index gate positions case for proper processing



"Clear" button for jams & replacing bottom tape roll

OPTIONS & ACCESSORIES



Swivel & locking casters



Tape head spare parts kit



Optional infeed and exit tables



IPG® is the only North American manufacturer of all 3 types of pressure sensitive adhesives. Combine Interpack™ machinery and IPG® long roll pressure sensitive tape for greater value. Contact your authorized IPG® distributor for details.

itape with



Machinery: **800-972-4675**
www.itape.com | E-mail: info@itape.com