

## MODEL P330

Battery Powered, Manual Heavy Duty Plastic Strapping Tool



## Features

- All new lithium ion battery technology featuring user friendly charge indicator
- Extended working range
- Easy strap threading
- Adjustable sealing time for high sealing efficiency
- Suitable for polypropylene polyester, plain and embos strapping
- Tension speeds as low as 2.8"/second (70mm/second)
- Easy tension adjustment, to ensure the right strap tension for safe operation
- The perfect hand held tool for applying ¾" and 1" heavy polyester strap from Samuel Strapping Systems.
  - Used to strap assorted Sheet Metal (ferrous and non ferrous)
  - Plate Glass, Coiled Metal and Wire
  - And much more

# Model P330

## Battery Powered Manual Plastic Strapping Tool

### Standard Features

Samuel Strapping Systems is proud to introduce the P330 hand held battery operated tool.

This robust tool provides unparalleled performance with tension ratings not previously attainable. Coupled with exceptional industry leading speed the P330 is the perfect hand held tool to apply our heavy ¾" and 1" polyester strap.

With the latest Lithium ion battery technology you can expect your tool to last longer in the field and recharge in a fraction of the time compared to traditional battery operated tools.

### Specifications

Dimensions:	Length: 395 mm – 14" Width: 137mm – 5" Height: 143mm – 5"
Weight:	5.7 kg / 12.6 lbs. (incl. battery)
Suitable strap qualities:	Polypropylene and Polyester, plain and embossed
Tension:	1200 – 6000 N (270 – 1350 lbs) individual adjustment (Max. tension depends on strap quality)
Average sealing strength:	approx. 75% of strap breaking strength (dependent on strap quality)
Tension speed in seconds:	70-87 mm/s (2.8-3.4"/s)

#### Seal Joint

The advanced friction welding sealing technology guarantees a high seal joint efficiency.

Item No.	Model	Strap Width		Strap Thickness		Max Tension		Tension	Speed
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.0254	P330/19/0 80-1.19	19	¾"	0.80-1.19	0.31-.047	6000	1350	70-87	2.8-3.4
43.0256	P330/19/1 20-1 53	19	¾"	1.20-1.53	0.47-.060	6000	1350	70-87	2.8-3.4
43.0262	P330/25/0.40-0.79	25	1"	0.40-0.79	0.16-.031	6000	1350	70-87	2.8-3.4
43.0264	P330/25/0 80-1.19	25	1"	0.80-1.19	0.31-.047	6000	1350	70-87	2.8-3.4
43.0266	P330/25/1 20-1 35	25	1"	1.20-1.35	0.47-.053	6000	1350	70-87	2.8-3.4

### Accessories/Charging Units

Item No.	Description	Voltage/Frequency
N5.4326	P330 spare battery (Accu Li-Ion)	28 VDC/3.0 Ah
N5.4437	P330 battery charger	120 V/60 Hz
P33 0120	Suspension bracket for alternating positions	
P32 0112	Suspension bracket for standard working position	
P33 0121	Wearing Sheet for Rough Surfaces	
P33 0122	Wearing Plate for Rough Surfaces	
P32 2061	Turning Button Kit	



**Recharging time:** approx. 1 hour  
**Battery life:** approx. 3000 charges